

















CONTAINER SPECIFICATIONS

	Interior Dimensions	Door Opening	Top Opening	Tare Weight	Cubic Capacity	Payload	RSA Road Limit
20' Dry Freight Container steel 	L: 5,898 mm W: 2,350 mm H: 2,390 mm	W: 2,340 mm H: 2,280 mm		2,200 kg 4,850 lbs	33.0 cbm. 1,179 cu. ft.	24,000 kg 54,673 lbs	21,800 kg
40' Dry Freight Container steel 	L: 12,035 mm W: 2,350 mm H: 2,393 mm	W: 2,339 mm H: 2,274 mm		3,700 kg 8,156 lbs	67.0 cbm. 2,393 cu. ft.	28,800 kg 63,491 lbs	20,300 kg
40' High Cube Dry Container steel 	L: 12,030 mm W: 2,350 mm H: 2,690 mm	W: 2,340 mm H: 2,579 mm		3,930 kg 8,663 lbs	76.0 cbm. 2,714 cu. ft.	28,570 kg 62,984 lbs	20,070 kg
45' High Cube Dry Container steel 	L: 13,556 mm W: 2,352 mm H: 2,695 mm	W: 2,340 mm H: 2,579 mm		4,590 kg 10,118 lbs	86.0 cbm. 3,071 cu. ft.	27,910 kg 61,529 lbs	19,410 kg
20' Reefer Container aluminium 	L: 5,440 mm W: 2,294 mm H: 2,237 mm	W: 2,286 mm H: 2,238 mm		2,750 kg 6,062 lbs	27.9cbm. 986 cu. ft.	24,250 kg 53,460 lbs	21,250 kg
40' Reefer Container aluminium 	L: 11,577 mm W: 2,294 mm H: 2,210 mm	W: 2,286 mm H: 2,238 mm		3,950 kg 8,708 lbs	58.7 cbm. 2,073 cu. ft.	28,550 kg 62,940 lbs	20,050 kg
40' High Cube Reefer Container aluminium 	L: 11,577 mm W: 2,294 mm H: 2,509 mm	W: 2,290 mm H: 2,535 mm		4,150 kg 9,148 lbs	67.0 cbm. 2,366 cu. ft.	28,350 kg 62,499 lbs	19,850 kg
45' High Cube Reefer Container aluminium 	L: 13,102 mm W: 2,286 mm H: 2,509 mm	W: 2,294 mm H: 2,535 mm		5,200 kg 11,463 lbs	75.4 cbm. 2,663 cu. ft.	27,300 kg 60,184 lbs	18,800 kg
20' Open Top Container steel 	L: 5,893 mm W: 2,346 mm H: 2,353 mm	W: 2,338 mm H: 2,273 mm	L: 5,488 mm W: 2,230 mm	2,200 kg 4,850 lbs	32.0 cbm. 1,143 cu. ft.	28,280 kg 62,344 lbs	21,800 kg
40' Open Top Container steel 	L: 12,056 mm W: 2,347 mm H: 2,379 mm	W: 2,343 mm H: 2,279 mm	L: 11,622 mm W: 2,214 mm	3,800 kg 8,377 lbs	67.0 cbm. 2,393 cu. ft.	28,700 kg 63,270 lbs	20,200 kg
20' Flat Rack Container 	L: 5,935 mm W: 2,398 mm H: 2,327 mm			2,560 kg 5,643 lbs		21,440 kg 47,265 lbs	21,440 kg
20' Collapsible Flat Rack Container 	L: 5,699 mm W: 2,418 mm H: 2,286 mm			2,970 kg 6,547 lbs		27,030 kg 59,589 lbs	21,030 kg
40' Flat Rack Container 	L: 12,080 mm W: 2,420 mm H: 2,103 mm			5,480 kg 12,080 lbs		25,000 kg 55,113 lbs	18,520 kg
40' Collapsible Flat Rack Container 	L: 12,064 mm W: 2,369 mm H: 1,943 mm			5,200 kg 11,463 lbs		39,800 kg 87,741 lbs	18,800 kg
20' Open Side/Open Top Container steel 	L: 5,928 mm W: 2,318 mm H: 2,257 mm	W: 2,286 mm H: 2,278 mm	L: 5,350 mm W: 2,138 mm	2,775 kg 6,117 lbs	31.0 cbm. 1,107 cu. ft.	21,255 kg 46,791 lbs	21,225 kg
40' Artificial Tweendeck 	L: 11,823 mm W: 2,197 mm			4,860 kg 10,714 lbs		39,580 kg 87,256 lbs	19,140 kg

The specifications above should serve as a guideline only. In the case of special requirements, please contact a Ziegler consultant at Tel: +27 (0) 11 394 4480